

## Overview and technical parameter of functional area

### 功能区总览与技术参数

功能区分布 FUNCTION AREA	楼层 Floor	功能设置 Function	数量 Qty	面积 (m <sup>2</sup> ) Area (m <sup>2</sup> )	
管理中心 Management center	一层 F1	管理大厅 Management hall	1	1,500	
		餐饮区 Catering area	1	3,000	
	二层 F2	航站楼 Airport terminal	1	2,000	
		接待大厅 Reception hall	1	2,000	
		商务大厅 Business hall	1	944	
		商务大厅会议室 Business meeting room	(1)70		
			(2)73		
商务大厅贵宾室 VIP room	(3)95				
	(6)150				
展厅 Exhibition hall	二层 F2	会议室 Meeting room	4	(A/B)179 (C/D)159	
	二层 Mezzanine	多功能厅会议室 Multi-function meeting room	2	585	

设施 Facility	规格 Specs
展厅面积 Exhibition area	A、B、C、D馆各1.2万平方米, 接待大厅2000平方米 12,000sqm for Hall A,B,C,D each,2,000sqm for reception hall
观众主入口 Main entrance for visitors	每馆2个,4.0m*2.4m 2X each pavilion,4.0m*2.4m
展品主入口 Main entrance for exhibits	每馆东或西侧2个, 4.0m*6.0m 5.2m*6.0m 2X each pavilion at east and west wing,4.0m*6.0m,5.2m*6.0m
展品辅助入口 Additional entrance for exhibits	每馆10个, 4.6m*4.85m*4.24m 10X each hall,4.6*4.85m*4.24m
供电系统 Distribution system	高压进户10KV HV lead-in 10kv
	高压单母线双回路(两路高压进户) HV single-bus dual circuit (2 HV lead-in)
	总容量10400KVA Total capacity 1,0400KVA
	单馆容量1000KVA(约850KW) Capacity per hall 1,000KVA (about 850KW)
	低压TN-S系统(俗称三相五线制) LV TN-S system (3-phase 5-wire system)
	低压三相380V LV 3-phase 380V
低压单相220V LV single-phase 220V	
频率50HZ Frequency 50HZ	
压缩空气 Compressed Air	有 Yes
展厅采光 Hall lighting	自然采光及灯光(阳光带屋顶) Natural light and lighting fixtures (sunbelt roof)
展厅净高 Clearance height	8m-15m
给排水口 Water supply	有 Yes
消防系统 Fire lighting	消防栓、喷淋、消防炮 Fire hydrant,sprayer,fire extinguishing cannon
空调 Air-conditioning	有 Yes
网络 Network	有 Yes
广播系统 Broadcast	有 Yes
应急照明 Emergency lighting	有 Yes
停车位 Parking	地面一层, 2500个 F1,2,500 parking spaces